

LIFTERS INOX 200

EFFICIENT BATTERY-POWERED LIFTERS IN STAINLESS STEEL FOR FOOD, PHARMA AND CLEAN ROOM (C+D) USE

Discover new **opportunities** and **increase** your work **efficiency** with a battery-powered Hovmand lifter. Created for GMP in food production, pharmaceuticals and clean room (C+D).

Ease of handling, ease of cleaning, and quiet operation will make your Hovmand lifters **efficient**, **trusted** and **safe** work tools.

The lifters are designed for use in confined surroundings. By handling items with as little work as possible and by using the right movements, you **eliminate** harmful work procedures.

WHY A HOVMAND LIFTER

- Speed
- Operation
- Maneuverability

LIFTING TOOLS (inox)

Platforms and forks for **boxes**. Booms and manipulators for **reels**. Grip, turn and tip tools for **drums** and **containers**. Special tools for **all purposes** on request.

CAPACITIES & LIFTING HEIGHTS

The lifting **capacities** is up to 200 kg with a stroke range from 1600 to 2000 mm.

LEGS AND WHEELS

We supply legs in different widths and lengths, depending on task. Front wheels are fixed or swivel, rear wheels are swivelling with brake.

MATERIAL

Mast and sledge in stainless steel with precision ball bearings. All parts are electro polished allowing for more thorough and easy cleaning.

LIFTING FUNCTION

The lifters are equipped with **strong**, **energy-efficient** 24V DC motors and are driven by stainless steel reinforced cam belts with no special **maintenance** required.

CONTROLS

The lifters are **easy to use** with a handheld remote control unit with spiral cord; battery-indicator, built-in charger and charge indicator.

SAFETY

All movable parts shielded, and the lifters have overload protection and a security clutch. **Intelligent** recharging.

WE IMPROVE OUR CUSTOMERS' WORKFLOW WITH INTELLIGENT LIFTING AND MOVING SOLUTIONS



Inox 200



Inox 200



Inox 200

HOVMAND

LIFTING & MOVING TECHNOLOGY

OPTIONAL CONTROLS

The stainless steel lifters from Hovmand are operated with a water proof remote control with spiral cord.



LEGS, WHEELS & BRAKES

Hovmand supplies legs in different widths and lengths, depending on task. Front wheels are fixed or swivel, rear wheels are swivelling with brake.

LIFTING TOOLS

Platform, plastic:	500 x 500 mm
Platform, stainless steel:	500 x 400 mm (LxW)
Boom:	500 x Ø60 mm
Double boom:	(2x) 500 x Ø32 mm
Boom with V-block:	330 mm
V-block for platform:	For reels
Reel manipulator:	Grips in the core of the reel - manual or electric
Grip and turn:	Grips outside the object & turn
Grip and tip:	Grips outside the object & tip

MATERIAL:

Stainless Steel type 1.4301 (AISI 304) - electro polished.
Can be supplied in IP65



	Inox 200
Material	Stainless Steel
Capacity max. (kg)	200
Weight ex. lifting tools (kg)	70
Lifting height/Mast height (mm)	1600/1970
Lifting height/Mast height (mm)	2000/2370
Lifting speed (mm/sec)	125
Batteries (V/Ah)	24/9
Charger/ charging time (Amps/hour)	2/5
Legs width (inner/outer - mm)	470, 550
Legs length (from mast mm)	650



HOVMAND
LIFTING & MOVING TECHNOLOGY